



Safely with personnel elevating platform

# Transportation

Transportable lift: \_\_\_\_\_ Transport vehicle: \_\_\_\_\_

Document filler's name: \_\_\_\_\_ Date: \_\_\_\_\_

\_\_\_\_\_

In order Out of order

1.	There are no loose objects in the working platform. There are no people in the working platform during trailing, lifting or transportation.		
2.	The working platform is set to transport position. The outriggers must be locked to transport position.		
3.	The load capacity and the bed are sufficient. A low bed transportation vehicle (lowloader or trailer) must be used when transporting lifts that weight over 10 tonnes. Then the balance point will be low enough.		
4.	The transportation vehicle is on a lateral surface. The rolling of the vehicle must be prevented.		
5.	The ramp is gradual enough, steady and flat. Notice the "sling effect" caused by the long boom of the lift in sudden movement and when crossing thresholds. Use safety harness.		
6.	When lifting a personnel lift, the lifting points and the lifting equipment must be adequate.		
7.	The binding equipment must be strong enough. When binding lifts that weight over 5 tonnes chains and tightener must be used. Check the condition and the validity of yearly inspection of the chains and the binding linens.		
8.	The wires of the wire lift system are in good condition and positioned properly over the rollers and supporting surfaces.		
9.	The tyres, lights and the luminous tags of the vehicle are in proper condition.		
10.	The weight of the towable vehicle must not exceed the allowed for the towing vehicle. The driver is conscious of the allowed towing- and driving speed.		